

STARFLOR

STARFLOR is a PVC composite floor tile with marbling design produced by high pressure impact process. With densely compacted surface and PUR coated, it improved wear and ease of maintenance.

PLACE RECOMMENDED

Housing, Office Administration, Education, Retail

Starflor



INSTALLATION

1. Preparing subfloor



Hard, level, dry, smooth, sound and clean

2. Laying method



2.1 Unpack tiles 24hrs. before laying



2.4 Press each tile into position



2.2 Trace a line perpendicular to the main entrance



2.5 Roll with 50kg roller



2.3 Apply adhesive to a few sq.m of subfloor in one quarter

For full specification, installation, and maintenance details, please refer to the handbook

MAINTENANCE

Initial cleaning



Remove loose debris



Low speed cleaning machine

Protection



Apply wax

Daily maintenance



Dry sweeping or remove dirt with a damp mop

Periodic maintenance



High speed cleaning machine

SPECIFICATION DETAILS

DESCRIPTION	European Norms			EN 649		
Total thickness	EN 428	mm	1.6	2.0	2.5	3.2
Total weight	EN 430	g/m ²	3200	4100	5000	6400
Width	EN 427	mm		304.80		
Length	EN 427	mm		304.80		
CLASSIFICATION	European Norms			EN 649		
European Norms	EN 685	class	23 - 31	32 - 41	34 - 43	34 - 43
Fire rating	EN ISO 9239-2	class			Bfl-S1	
	DIN 4102	class			B1	
Sound insulation	EN ISO 717/2	dB			3	
	EN 140-8	dB (A)			3,2	
PERFORMANCE	European Norms			EN 649		
Density	EN 436	g/cm ³			2.15	
Abrasion	EN 660-1	mm			0.30	
Abrasion group	EN 649	class			F	
Dimensional stability	EN 434	%			<0.20	
Incurvation after 6 h at 80 C°	EN 434	mm			0.30	
Residual indentation	EN 433	mm			0.05	
Staining resistance	EN 423	X			Good	
Colour fastness	EN 20 105-B02	degree			6	

STARFLEX®

UNION PROPERTY CO., LTD. 88/44 Soi Ngamvongwan 2 (Akkane), Ngamvongwan Rd., Bangkok, Muang, Nonthaburi 11000. THAILAND
 Tel. +66-(0)2580-0620, (0)2951-0710-4 Fax. +66-(0)2580-4557, (0)2951-0718
 Website: www.starflexile.com E-mail: sales@starflexile.com, export@starflexile.com