Self-Contained Extractor EX-SC-3840



Sleek design and reliable performance in a self contained carpet extractor.

ENNAN

This carpet extractor allows for the exact amount of agitation to remove tough soil without causing damage. The ergonomic handle grip and fingertip solution controls minimise hand movement during operation and allow for hours of comfortable operation. The brush meter allows the operator to adjust for optimal brush height.

Durable construction, reliable performance

Constructed of durable polyethylene that resists dents and cracks, this extractor is built to last and can withstand the demands of everyday extracting.

Greater maneuverability

This extractor is perfect for cleaning in confined areas like classrooms, office buildings, hospitals and restaurants as well as larger open areas.

Key Benefits

- Brush scrub deck with large motor and stiff brush coupled with dual spray nozzles provide outstanding cleaning performance
- Ergonomic handle with trigger solution control allows for comfortable operation
- This unit moves easily with its lightweight yet durable construction and low centre of-gravity bladder system

EX-SC-3840 AU/NZ 09/10

©2010 Tennant is a registered trademark of Tennant Company, whose products are sold and serviced through Tennant Sales and Service Company, as well as through distributors.

Tennant Australia

Unit 2, Block Y, 391 Park Road (PO Box 116) Regents Park NSW 2143 Toll Free: 1800 226 843 Ph: +61 8718 9718 Fax: +61 8718 9719 www.tennantco.com.au contactus@tennantco.com

Tennant New Zealand

Unit 5, 103 Cryers Road East Tamaki Auckland 2013 Ph: +64 9 253 9013 Fax: +64 9 253 9015 www.tennantco.co.nz contactus@tennantco.com



Self-Contained Extractor EX-SC-3840



Features	Specifications*
Product Name	EX-SC-3840
Vacuum System Vacuum motor HP Vacuum motor stages Water lift at sealed orifice Airflow through 2 in / 50 mm orifice Vacuum shoe size	1.8 hp / 1.4 kW 2 stage 3480 mm 101 cfm / 2.89 m ³ 510 mm
Recovery System Recovery tank capacity Recovery tank description	55 L Integrated bladder tank
Brush Drive System Brush motor amp Brush RPM Brush motor RPM Brush width Brush bristle type Brush diameter	1 A 1200 1800 508mm Nylon construction, four rows of bristles arranged with 360 degrees spiral 84 mm
Solution System Solution pump amps Solution pump pressure Solution pump voltage Solution capacity Solution flow Solenoid valve Spray jets	1 A 100 psi / 7 Bar 240 V 38 L 3.8 L / min Electric Quarter turn, quick disconnect
Total Power Consumption	14.2 A / 1710 watts
Power Cord Power cord length Power cord type	15 m 16 guage
Optional Accessories	Various wands, hand tools, solution and recovery hoses, etc.
Dimensions/Weight/Sound Level Length/Width/Height/Weight/Sound	L: 1092 mm, W: 406 mm, H: 864 mm, Wt: 42 kg, >70 dBA (@ operators ear)
Warranty	See your sales representative or authorised distributor for complete warranty details.

*Specifications subject to change without notice

Tennant Australia

Unit 2, Block Y, 391 Park Road (PO Box 116) Regents Park NSW 2143 Toll Free: 1800 226 843 Ph: +61 8718 9718 Fax: +61 8718 9719 www.tennantco.com.au contactus@tennantco.com

Tennant New Zealand

Unit 5, 103 Cryers Road East Tamaki Auckland 2013 Ph: +64 9 253 9013 Fax: +64 9 253 9015 www.tennantco.co.nz contactus@tennantco.com

EX-SC-3840 AU/NZ 09/10

©2010 Tennant is a registered trademark of Tennant Company, whose products are sold and serviced through Tennant Sales and Service Company, as well as through distributors.