

# Canister Extractor



**Portable low and adjustable carpet extractor makes quick work in tight areas.**

### **Simple maintenance, easy mobility**

Get quick, easy access to working parts with the convenient clamshell design. The extractor's large rear wheels increase mobility and allow for easier transportation on stairs.

### **Low cost life-cycle**

Strong and robust construction means years of dependable use. The unique bladder design maximises solution/recovery while minimising the unit's footprint.



## Key Benefits

- Straight forward, simple design makes this unit easy to use and maneuver
- Patented bladder design keeps machine compact
- Standard 100 psi /6.9 bar unit is easy to transport and perfect for cleaning in both tight or open spaces

### **Tennant Australia**

Unit 2, Block Y, 391 Park Road (PO Box 116)  
Regents Park NSW 2143  
Toll Free: 1800 226 843  
Ph: +61 8718 9718  
Fax: +61 8718 9719  
[www.tennantco.com.au](http://www.tennantco.com.au)  
[contactus@tennantco.com](mailto:contactus@tennantco.com)

### **Tennant New Zealand**

Unit 5, 103 Cryers Road  
East Tamaki Auckland 2013  
Ph: +64 9 253 9013  
Fax: +64 9 253 9015  
[www.tennantco.co.nz](http://www.tennantco.co.nz)  
[contactus@tennantco.com](mailto:contactus@tennantco.com)



# Canister Extractors



Features	Specifications*
<b>Product Name</b>	EX-CAN-57-LP (low pressure)
<b>Solution System</b> Solution pump pressure Solution pump voltage Solution pump amps Solution pump open flow rate	100 psi / 6.9 bar 220 V .5 A 6.81 L/min
<b>Vacuum System</b> Airflow at 2 in / 50 mm orifice Water lift at sealed orifice Vacuum motor type	2.8 m <sup>3</sup> /h 3480 mm Single speed, tangential discharge, 145 mm diameter, dual ball bearings, epoxy painted fan case; recognised by UL
Vacuum motor power Vacuum motor stages Vacuum motor voltage Vacuum motor amps	1.66 hp / 1.23 kW 3 stage 220 V AC 6.8 A
<b>Tank Capacity</b> Solution tank capacity Recovery tank capacity	56.7 L 71.9 L
<b>Chassis/Body Construction</b> Construction type Caster diameter (locking) Wheel diameter	Rotationally-molded polyethylene 100 mm 305 mm
<b>Power Cord</b> Power cord length Power cord type	7.6 m, 1 cord 14 gauge 3 wire SJTO, recognised by UL and CSA, safety yellow, detachable
<b>Standard Tools/Accessories</b> Tool/accessory description	Low pressure (EX-CAN-15 LP) 330 mm floor tool with three spray jets, stainless steel wand/shoe, 4.5 m x 380 mm vacuum hose, 4.5 m x 90 mm solution hose Contact your sales representative or authorised distributor for information on additional accessories.
<b>Dimensions/Weight/Sound Level</b> Length/Width/Height/Weight/Sound	L: 965 mm, W: 482 mm, H: 965 mm, Wt: 1149.8 kg, 82 dBA
<b>Warranty</b>	See your sales representative or authorised distributor for complete warranty details.

\*Specifications subject to change without notice

## Tennant Australia

Unit 2, Block Y, 391 Park Road (PO Box 116)  
Regents Park NSW 2143  
Toll Free: 1800 226 843  
Ph: +61 8718 9718  
Fax: +61 8718 9719  
www.tennantco.com.au  
contactus@tennantco.com

## Tennant New Zealand

Unit 5, 103 Cryers Road  
East Tamaki Auckland 2013  
Ph: +64 9 253 9013  
Fax: +64 9 253 9015  
www.tennantco.co.nz  
contactus@tennantco.com

EX-CAN-57-LP AU/NZ 09/10

©2010 Tennant is a registered trademark of Tennant Company, whose products are sold and serviced through Tennant Sales and Service Company, as well as through distributors.