

All Surface Cleaner



Keep restrooms and hard surfaces sparkling clean with the 'All Surface Cleaner'.

The All Surface Cleaner is the right solution for the number one cleaning challenge—restrooms. It's also a great match for cleaning other hard surfaces like stairwells, windows and more.

Multifunctional cleaner

The All Surface Cleaner cleans and rinses fixtures and surfaces, blow dries the rinsed surfaces and then recovers dirty water without the operator touching a surface. After cleaning, the recovery tank easily empties using a drop-down drain hose or power pump-out system.

Tools and accessories

This portable cleaner comes complete with ten standard tools and accessories, including a telescopic vacuum wand and a separate expandable clean-air blower hose.



Key Benefits

- Replace your mop and bucket with the All Surface Cleaner, which is the preferred solution for cleaning restrooms and other hard surfaces
- Increase productivity, employee safety, and morale with this touch-free method of cleaning
- Ideal for use on sinks, toilets, urinals, shower stalls and other non-porous surfaces in change rooms, restrooms, stairwells and more

Tennant Australia

Unit 2, Block Y, 391 Park Road (PO Box 116)
Regents Park NSW 2143
Toll Free: 1800 226 843
Ph: +61 8718 9718
Fax: +61 8718 9719
www.tennantco.com.au
contactus@tennantco.com

Tennant New Zealand

Unit 5, 103 Cryers Road
East Tamaki Auckland 2013
Ph: +64 9 253 9013
Fax: +64 9 253 9015
www.tennantco.co.nz
contactus@tennantco.com



All Surface Cleaner



Features	Specifications*
Product Name	ASC-57
Vacuum/Recovery System Airflow at 50 mm orifice Water lift at sealed orifice Vacuum motor type Vacuum motor amps Vacuum motor stages Vacuum motor voltage Vacuum motor watts	99 cfm / 2.8 m ³ /hr 2982 mm Single speed, tangential discharge, 144 mm diameter, dual ball bearings epoxy painted fan case, recognised by UL 10 A 3 stage 220 V 1200 watts
Solution/Recovery Tanks Solution tank capacity Recovery tank capacity	56.7 L 71.9 L
Blower System Motor (1) Water lift at sealed orifice Vacuum motor type Vacuum motor amps Vacuum motor stages Vacuum motor voltage Vacuum motor watts	Separate blower motor 2311 mm Single speed, UL, CSA 7.3 A 2 stage 220 V 1566 watts
Power System Power cord length Power cord type	15 m GFCI 14 gauge, 3 wire, SJTO: recognised by UL and CSA, non-marking safety yellow
Dimensions/Weight/Sound level Height Width Length Net weight Sound level (operator's ear)	953 mm 470 mm 927 mm 57 kg 82 dBA
Standard Equipment	Two-piece 7.6m telescopic aluminum vacuum wand, 38 mm diameter recovery hose (black), 7.6 m expandable gray clean air blower hose, 7.6 m high pressure hose with quick-connect variable pressure gun, scrub brush, floor squeegee tool, hand squeegee tool, blower tool, gulper floor drain tool, chemical metering tip packet, fill hose
Warranty	See your sales representative or authorised distributor for complete warranty details.

*Specifications subject to change without notice

Tennant Australia

Unit 2, Block Y, 391 Park Road (PO Box 116)
Regents Park NSW 2143
Toll Free: 1800 226 843
Ph: +61 8718 9718
Fax: +61 8718 9719
www.tennantco.com.au
contactus@tennantco.com

Tennant New Zealand

Unit 5, 103 Cryers Road
East Tamaki Auckland 2013
Ph: +64 9 253 9013
Fax: +64 9 253 9015
www.tennantco.co.nz
contactus@tennantco.com

ASC-57 AU/NZ 09/10

©2010 Tennant is a registered trademark of Tennant Company, whose products are sold and serviced through Tennant Sales and Service Company, as well as through distributors.