



8w **14w** **21w** **28w**

DIMENSION (mm)

Model	A	B	C	D	E	Weight(g)
Slimset 8W T5	314	288	25	41	20	161
Slimset 14W T5	573	549	25	41	20	256
Slimset 21W T5	873	849	25	41	20	358
Slimset 28W T5	1173	1149	25	41	20	478

SPECIFICATION OF ELECTRONIC BALLAST

Reference	Slimset 8W	Slimset 14W	Slimset 21W	Slimset 28W
For Lamp	8W	14W	21W	28W
Supply Voltage (V)	220-240	220-240	220-240	220-240
Lamp Start (sec)	< 0.5	< 0.5	< 0.5	< 0.5
Supply Frequency (Hz)	50/60	50/60	50/60	50/60
Operating Frequency (KHz)	25 - 50	25 - 50	25 - 50	25 - 50
Supply Current at 220V (A)	0.061	0.106	0.130	0.159
Power Factor	0.60	0.60	0.60	0.98
Total Harmonic Distortion (%)	-	-	-	12
System Wattage At 220V (W)	8	14	21	28
Ambient Temp. Range	-5 °c-50 °c	-5 °c-50 °c	-5 °c-50 °c	-5 °c-50 °c
Temperaure Control (°C)	80	80	80	80
EMC	TIS 1955-2542	TIS 1955-2542	TIS 1955-2542	TIS 1955-2542
Safety Lamp Holder	TIS 344-2549	TIS 344-2549	TIS 344-2549	TIS 344-2549



ISO 9001-2008

ISO 14001-2004

ISO 14001-2004

SAFETY MANAGEMENT SYSTEM

ENVIRONMENTAL MANAGEMENT SYSTEM

ENERGY STAR 5