



Technical data

| Ex-e Cable glands Blanking plugs Reducing rings | |
|---|---|
| Marking to 94/9/EC | Ⓔ II 2 G Ex e II / Ⓔ II 2 D Ex tD A21 IP66 |
| EC-Type Examination Certificate of conformity | M12-M16: PTB 99 ATEX 3101 X / M20-M63: PTB 99 ATEX 3128 X |
| IECEX Certification of conformity | IECEX PTB 05.0004X |
| Marking accd. to IECEX | Ex e II |
| Permissible ambient temperature | -20 °C to +70 °C -55 °C to +70 °C option ¹⁾ |
| Degree of protection accd. EN 60529 | IP66 / IP68: 1 m water depth for 0.5 h |
| Enclosure material | Polyamide |

| Ex-e Screw plug | |
|---|--|
| Marking to 94/9/EC | Ⓔ II 2 G Ex e II / Ⓔ II 2 D Ex tD A21 IP66 |
| EC-Type Examination Certificate of conformity | M20-M50: PTB 98 ATEX 3130 / M63: PTB 03 ATEX 1058 (nur II 2 G) |
| IECEX Certification of conformity | IECEX PTB 03.0000 (M20 - M50) |
| Marking accd. to IECEX | Ex e II |
| Permissible ambient temperature | M20-M50: -55 °C to +55 °C / M63: -20 °C to +55 °C |
| Degree of protection accd. EN 60529 | IP66 / IP68: 1 m water depth 0.5 h |
| Enclosure material | Polyamide |

¹⁾ Low temperature cable gland on request