



Reducing ring

Screw plug

Blanking plug

Ordering details

For cable gland	Ø A mm	Length B mm	Weight approx. kg	OU	Order No. (-20 °C up to 70 °C)
Blanking plug					
M12	6.0	30.3	0.001	20	GHG 960 1944 R0101
M16	7.0	33.0	0.001	20	GHG 960 1944 R0102
M20	8.5	34.5	0.002	20	GHG 960 1944 R0103
M25	11.0	36.0	0.003	20	GHG 960 1944 R0104
M32	14.0	39.5	0.005	20	GHG 960 1944 R0105
M40	20.0	42.0	0.018	10	GHG 960 1944 R0106
M50	26.0	44.0	0.033	10	GHG 960 1944 R0107
M63	34.0	45.0	0.108	5	GHG 960 1944 R0108

Thread	Ø D mm	Length A mm	Length B mm	Weight approx. kg	OU	Order No.
Screw plug						
M16 x 1.5	21.5	4.0	12	0.002	20	GHG 960 1952 R0111
M20 x 1.5	25.5	4.0	13	0.004	20	GHG 960 1952 R0112
M25 x 1.5	30.5	4.0	13	0.007	20	GHG 960 1952 R0113
M32 x 1.5	37.5	5.5	15	0.013	10	GHG 960 1952 R0114
M40 x 1.5	45.5	5.5	15	0.020	10	GHG 960 1952 R0115
M50 x 1.5	55.5	5.5	16	0.030	5	GHG 960 1952 R0116
M63 x 1.5	85	6.5	16	0.040	5	GHG 960 1952 R0117

Thread 1	Thread 2	L1 mm	L2 mm	L3 mm	AF mm	Weight approx. kg	OU	Order No.
Reducing rings								
M20 x 1.5	M16 x 1.5	12	8	8	24	0.014	20	GHG 960 1946 R0071
M25 x 1.5	M20 x 1.5	14	8	8	29	0.016	20	GHG 960 1946 R0072
M32 x 1.5	M20 x 1.5	16	10	6	36	0.017	20	GHG 960 1946 R0056
M32 x 1.5	M25 x 1.5	16	10	10	36	0.016	20	GHG 960 1946 R0074
M40 x 1.5	M25 x 1.5	16	10	8	46	0.023	10	GHG 960 1946 R0059
M40 x 1.5	M32 x 1.5	16	10	10	46	0.021	10	GHG 960 1946 R0077
M50 x 1.5	M32 x 1.5	18	12	10	55	0.036	10	GHG 960 1946 R0062
M50 x 1.5	M40 x 1.5	18	12	10	68	0.032	10	GHG 960 1946 R0080
M63 x 1.5	M40 x 1.5	18	12	10	68	0.040	5	GHG 960 1946 R0065
M63 x 1.5	M50 x 1.5	18	12	12	68	0.030	5	GHG 960 1946 R0083

Cable glands with PG-thread are available on request.

The order No. will show 1 pcs.

Please note that only order units (OU) can be ordered.