



MACHINERY WORKS CO., LTD.

High Speed Band Saw, Variable Speed, Enlarged Speed Range (50-5200 Ft/Min)

V-2012-H (HYDRAULIC TABLE)



SPECIFICATIONS

Throat Depth	20" (500mm)
Work Height	12" (304mm)
Blade Width	1/8" thru 1" (3 thru 25mm)
Blade Length	161-3/8" (4100mm)
Bandwheel Dimensions	20-1/2" x 1-3/4" (520 x 44mm)
Bandwheels Number	2
Wheel Tires	Easily Replacable Rubber Tires
Table Type	Hydraulic Powered
Main Table Size	26-3/4" x 29" (679 x 736mm)
Table Tilt	30° R, 15° L
Table Workheight	40-1/2" (1028mm)
Blade Drive Motor	3 HP
Electric Controls	Mag Motor Starters, 115 Volt Controls
Blade Speed	50-5200 fpm (15-1575 mpm)
Transmission	Totally Enclosed
Blade Welder, Grinder, Shear	1" Capacity, Standard Equipment
Table Stroke	13" (330mm)
Dimension:	
Length	51" (1295mm)
Width	44" (1117mm)
Height	81" (2057mm)
Net Weight	1870 lbs (850 kgs)

STANDARD FEATURES:

115V control circuit, motor overload and under volt protection, chevron blade guides 1/16" up to 1", blade tension, variable blade speed 50-5200 SFPM (15-1575 MPM), rip fence, chip blower, blade welder, grinder, shear & digital speed meter.