



MACHINERY WORKS CO., LTD.

## High Speed Band Saw, Variable Speed, Enlarged Speed Range (50-5200 Ft/Min)

### V-2812-H (HYDRAULIC TABLE)



#### SPECIFICATIONS

<b>Throat Depth</b>	28" (700mm)
<b>Work Height</b>	12" (304mm)
<b>Blade Width</b>	1/8" thru 1" (3 thru 25mm)
<b>Blade Length</b>	198" (5030mm)
<b>Bandwheel Dimensions</b>	28-3/8" x 1-3/4" (720 x 44mm)
<b>Bandwheels Number</b>	2
<b>Wheel Tires</b>	Easily Replacable Rubber Tires
<b>Table Type</b>	Hydraulic Powered
<b>Main Table Size</b>	26-3/4" x 29" (679 x 736mm)
<b>Table Tilt</b>	30° R, 15° L
<b>Table Workheight</b>	42" (1069mm)
<b>Blade Drive Motor</b>	3 HP
<b>Electric Controls</b>	Mag Motor Starters, 115 Volt Controls
<b>Blade Speed</b>	50-5200 fpm (15-1575 mpm)
<b>Transmission</b>	Totally Enclosed
<b>Blade Welder, Grinder, Shear</b>	1" Capacity, Standard Equipment
<b>Table Stroke</b>	13" (330mm)
<b>Dimension:</b>	
<b>Length</b>	61-3/8" (1560mm)
<b>Width</b>	44" (1117mm)
<b>Height</b>	90-3/4" (2307mm)
<b>Net Weight</b>	2310 lbs (1050 kgs)

#### STANDARD FEATURES:

115V control circuit, motor overload and under volt protection, chevron blade guides 1/16" up to 1", blade tension, variable blade speed 50-5200 SFPM (15-1575 MPM), rip fence, chip blower, blade welder, grinder, shear & digital speed meter.