

**Ex-Portable outlet distribution: 16A 3-pole, 5-pole**



**Technical data**

| 16A 3-pole   16A 5-pole                                     |  |
|---|--|
| Marking to 94/9/EC  | $\text{Ex}$ II 2 G Ex ed IIC T6  |
| EC-Type Examination Certificate                             | PTB 02 ATEX 1035   |
| Permissible ambient temperature                             | -20 °C to +40 °C <sup>1)</sup>   |
| Rated voltage   | 3-pole 16 A: to 500 V / 5-pole 16 A: to 400 V  |
| Rated current   | 16 A   |
| Frequency   | 50/60 Hz   |
| Rated making-/breaking capacity AC-3<br>accd. to EN 60947-3 | $U_e$ 690 V / $I_e$ 16 A   |
| External back up fuse                                       | without thermal protection: 16 A<br>with thermal protection: 25 A gL (rated current 16 A set to) |
| Degree of protection accd. EN 60529                         | IP66   |
| Cable glands/enclosure drilling                             | Trumpet shaped cable gland M32   |
| Weight  | with 2 m connecting cable: 4.2 kg / with 5 m connecting cable 5.2 kg                             |
| Enclosure material  | Socket distribution: Glass-fibre reinforced polyester<br>Plug and flange socket: polyamide       |
| Enclosure colour  | Black  |

<sup>1)</sup> extended temperature range on request