

CCH PART NUMBER		XLH 303020	XLH 403020	XLH 404020	XLH 405020	XLH 504020	XLH 505020	XLH 506020	XLH 604020	XLH 605020	XLH 606020	XLH 607620	XLH 765020	XLH 766020	XLH 767620
DIMENSIONS OVERALL, mm	(HEIGHT X WIDTH X DEPTH)	306 x 306 x 203	406 x 305 x 203	406 x 406 x 203	406 x 508 x 203	508 x 406 x 203	508 x 508 x 203	508 x 610 x 203	610 x 406 x 203	610 x 508 x 203	610 x 610 x 203	610 x 762 x 203	762 x 508 x 203	762 x 610 x 203	762 x 762 x 203
	(Imperial Conversion)	(12" x 12" x 8")	(16" x 12" x 8")	(16" x 16" x 8")	(16" x 20" x 8")	(20" x 16" x 8")	(20" x 20" x 8")	(20" x 24" x 8")	(24" x 16" x 8")	(24" x 20" x 8")	(24" x 24" x 8")	(24" x 30" x 8")	(30" x 20" x 8")	(30" x 24" x 8")	(30" x 30" x 8")
Hoffman Range Equivalent		---	C-SD16128SS6	C-SD16168SS6	C-SD16208SS6	C-SD20168SS6	C-SD20208SS6	---	C-SD24168SS6	C-SD24208SS6	C-SD24248SS6	---	---	C-SD30248SS6	C-SD30308SS6
"Concept" - CWS (Type 316L)		---	A-16H1208SS6LP	---	---	A-20H1608SS6LP	A-20H2008SS6LP	A-20H2408SS6LP	A-24H1608SS6LP	A-24H2008SS6LP	A-24H2408SS6LP	A-24H3008SS6LP	A-30H2008SS6LP	A-30H2408SS6LP	A-30H3008SS6LP
"Type 4X" - A4S (Type 316L)		---	---	---	---	---	---	---	---	---	---	---	---	---	---
FIXING CENTRES, mm	Vertical	203	267	267	267	354	354	354	445	445	445	445	508	508	508
	Horizontal	361	361	462	564	462	564	666	462	564	666	818	564	666	818
MATERIAL THICKNESS, mm	BODY	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	DOOR	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
WEIGHT (empty)	kg	5.8 kg	6.6 kg	8.1 kg	9.7 kg	9.7 kg	11.4 kg	13.2 kg	11.2 kg	13.2 kg	15.3 kg	18.3 kg	15.9 kg	18.3 kg	21.9 kg
TERMINAL MOUNTING RAIL															
RAIL FIXING CENTRES, mm	VERT	206	306	306	306	408	408	408	510	510	510	510	662	662	662
	HORZ	206	205	306	408	306	408	510	306	408	510	662	408	510	662
RAIL LENGTH, mm	VERT	226	326	326	326	428	428	428	530	530	530	530	682	682	682
	HORZ	226	225	326	428	326	428	530	326	428	530	682	428	530	682
AVAILABLE GLANDING AREA , mm															
(with Gland Plates FITTED)	TOP & BOTTOM	261 x 124	261 x 124	334 x 124	460 x 124	334 x 124	460 x 124	562 x 124	334 x 124	460 x 124	562 x 124	714 x 124	460 x 124	562 x 124	714 x 124
	LEFT & RIGHT	214 x 124 (L) 261 x 124 (R)	261 x 124	261 x 124	261 x 124	334 x 124	334 x 124	334 x 124	460 x 124	460 x 124	460 x 124	460 x 124	562 x 124	562 x 124	562 x 124
MAXIMUM ENTRY GUIDE (Metric Glands)															
	M16	34	34	44	62	44	62	78	44	62	78	100	62	78	100
	M20	18	18	26	35	26	35	44	26	35	44	56	35	44	56
	M25	15	15	21	29	21	29	36	21	29	36	47	29	36	47
	TOP & BOTTOM														
	M32	8	8	11	15	11	15	19	11	15	19	24	15	19	24
	M40	6	6	9	13	9	13	16	9	13	16	20	13	16	20
	M50	3	3	4	5	4	5	7	4	5	7	9	5	7	9
	M63	2	2	3	4	3	4	5	3	4	5	7	4	5	7
	M16	28 (L) / 34 (R)	34	34	34	44	44	44	62	62	62	62	78	78	78
	M20	15 (L) / 18 (R)	18	18	18	26	26	26	35	35	35	35	44	44	44
	M25	12 (L) / 15 (R)	15	15	15	21	21	21	29	29	29	29	36	36	36
	M32	6 (L) / 8 (R)	8	8	8	11	11	11	15	15	15	15	19	19	19
	M40	5 (L) / 6 (R)	6	6	6	9	9	9	13	13	13	13	16	16	16
	M50	2 (L) / 3 (R)	3	3	3	4	4	4	5	5	5	5	7	7	7
	M63	2 (L) / 2 (R)	2	2	2	3	3	3	4	4	4	4	5	5	5
TERMINAL CONTENT															
	Terminal Size Orientation in Enclosure														
	2.5 mm2	VERT	2 x 36	2 x 56	3 x 56	4 x 56	3 x 77	4 x 77	6 x 77	3 x 97	4 x 97	6 x 97	7 x 97	4 x 128	6 x 128
	4 mm2	VERT	2 x 30	2 x 47	3 x 47	4 x 47	3 x 64	4 x 64	6 x 64	3 x 81	4 x 81	6 x 81	7 x 81	4 x 106	6 x 106
	6 mm2	VERT	2 x 23	2 x 35	3 x 35	4 x 35	3 x 48	4 x 48	6 x 48	3 x 61	4 x 61	6 x 61	7 x 61	4 x 80	6 x 80
	10 mm2	VERT	2 x 18	2 x 28	3 x 28	4 x 28	3 x 38	4 x 38	6 x 38	3 x 49	4 x 49	6 x 49	7 x 49	4 x 64	6 x 64
	16 mm2	VERT	2 x 15	2 x 23	3 x 23	4 x 23	3 x 32	4 x 32	6 x 32	3 x 40	4 x 40	6 x 40	7 x 40	4 x 53	6 x 53

- NOTES : -
- The information provided is based on the physical constraints of the enclosure. Please refer to the certificate for hazardous area applications.
  - This information is for guidance purposes only. Cooper Crouse-Hinds UK Ltd reserves the right to make any necessary changes without notice