

1/3" Sharp CCD, 420 TV Lines

FEATURE

- Pick-up device : 1/3" SHARP CCD
- Resolution : more than 420 TVLines
- Min. illumination : 1.0 LUX
- AGC, BLC



CCD DOME CAMERA



SPECIFICATIONS

Model	TC-552C
Pick-up Device	1/3" Sharp CCD
Number of Pixels	PAL : 500Hx582(V)
Horizontal Resolution	420 TVLines
Minimum illumination	1.0 LUX
S/N Ratio	>48dB
White Balance	N/A
Auto gain Control	Auto
Backlight Compensation	Auto
Exposure Mode	EE
Electronic Shutter	1/50-1/100,000 SEC
Video Output	1.0V/p-p composite video, 75Ω
Gamma Correction	0.45
Synchronizing System	Internal
Lens	Build-in
Supply Voltage	DC12V
Operation temperature	-10°C to 50°C

TC-580CH-DN

Day/Night Dome Camera

TELCA


1/3" SONY Super HAD II CCD, 540 TV Lines



FEATURE

- Pick-up device : 1/3" SONY Super HAD II CCD
- Resolution : more than 540 TVLines
- Min. illumination : 0.01 LUX
- AGC, Auto White Balance

CCD DOME CAMERA



SPECIFICATIONS

Model	TC-580CH-DN
Pick-up Device	1/3" SONY Super HAD II CCD
Number of Pixels	PAL : 752(9)x582(V)
Horizontal Resolution	540 TVLines
Minimum illumination	0.01 LUX/F1.2
S/N Ratio	≥48dB
White Balance	On/Off Switchable
Auto gain Control	On/Off Switchable
Backlight Compensation	On/Off Switchable
Exposure Mode	EE/AI Switchable
Electronic Shutter	1/50-1/100,000 SEC
Video Output	1.0Vp-p composite video, 75Ω
Gamma Correcton	0.45
Synchronizing System	Internal
Lens	C/CS
Supply Voltage	DC12V
Operation temperature	-10°C to 50°C

1/3" SONY Super HAD II CCD, 420 TV Lines

FEATURE

- Pick-up device: 1/3" Sony Super HAD CCD
- Resolution: more than 420 TV lines
- Min. Illumination: 0.01 LUX/F1.2
- A/WB, AGC, BLC
- Supply voltage: DC 12V



SPECIFICATIONS


Model	TC-530C-DN
Pick-up Device	1/3" SONY Super HAD II CCD
Number of Pixels	PAL: 500Hx582V)
Horizontal Resolution	420 TV Lines
Minimum Illumination	0.01 LUX/F1.2
S/N Ratio	≥48dB
White Balance	Auto
Auto gain Control	Auto
Backlight Compensation	Auto
Exposure Mode	EE
Electronic Shutter	1/50-1/100,000 SEC
Video Output	1.0V/p-p composite video, 75Ω
Gamma Correction	0.45
Synchronizing System	Internal
Lens	C/CS Mount
Supply Voltage	DC12V
Operation temperature	-10°C to 50°C

1/3" Sony super HAD CCD Dome Camera 420 TVL, 0.8 LUX



FEATURE

- Pick-up device : 1/3" Sony super HAD CCD
- Resolution : more than 420 TVLines
- Min. illumination : 0.8 LUX
- AGC, Auto White Balance



SPECIFICATIONS

Model	TC-531F
Pick-up Device	1/3" Sony super HAD CCD
Number of Pixels	PAL : 500p(6382V)
Horizontal Resolution	420 TVLines
Minimum illumination	0.8 LUX
S/N Ratio	More than 48dB
White Balance	Auto
AGC	Auto
Backlight Compensation	Auto
Exposure Mode	EE
Electronic Shutter	1/50,1/60,1/100,000 SEC
Video Output	1.0Mp-p composite video, 75Ω
Gamma Correcton	0.45
Synchronizing System	Internal
Lens	Build-in
Supply Voltage	DC12V
Operation temp.	-10°C to 50°C

1/3" SONY Super HAD II CCD, 420 TV Lines

FEATURE

- Pick-up device: 1/3" SONY Super HAD II CCD
- Resolution: more than 420 TV lines
- Min. Illumination: 0.8 LUX/F1.2
- ATW, AGC, BLC
- Supply voltage: DC 12V



SPECIFICATIONS

Model	TC-535
Pick-up device	1/3"SONY Super HAD II CCD
Number of pixels	PAL : 500 (H) x582(V)
Horizontal resolution	420 TVLines
Minimum illumination	0.8 LUX/F1.2
S/N ratio	>48dB
White Balance	Auto
Auto gain control	Auto
Backlight compensation	Auto
Exposure Mode	EE
Electronic shutter	1/50~1/100000 SEC
Video output	1.0Vp-p composite video,75Ω
Gamma Correction	0.45
Synchronizing System	Internal
Lens	Build-in
Supply voltage	DC12V
Operation temperature	-10°C to 50°C