

N-61



Standardlänge *	ca. 50 + 100 m (- 3 / + 5 m)
Standardbreite **	50, 70, 100 mm
Trägergewebe	99/1% BW/PES L 1/1 18/14 – 20,2/20,2 Nm
Art der Beschichtung	Naturkautschuk
Beschichtungshärte	ca. 42° Shore A (+/- 5°)
Farbe	beige
Gewicht m ²	ca. 1.600 g
Stärke	1,9 mm +/- 0,15 mm
<u>Reißfestigkeit des Trägers:</u>	
Kette	>1200 N/5 cm
Schuß	>1100 N/5 cm
Trennlasten (Träger/Beschichtung)	>90 N/5 cm
Temperaturbeständigkeit	ca. 100 °C
Abrieb (DIN 53516)	<300 mm ³
<u>Beständigkeit gegen:</u>	<input checked="" type="checkbox"/> Säuren <input checked="" type="checkbox"/> Laugen <input checked="" type="checkbox"/> Öle <input checked="" type="checkbox"/> Fette <input checked="" type="checkbox"/> Heißwasser
Sonderausrüstung	-

* andere Längen auf Anfrage
 ** andere Breiten auf Anfrage

Diese Informationen wurden zu Ihrer Unterrichtung und Beratung nach unseren Erfahrungen und bestem Wissen gegeben. Der Inhalt ist jedoch ohne Rechtsverbindlichkeit. Die angegebenen Daten wurden nach hausinternen Testmethoden ermittelt; um jedoch die Verwendbarkeit gemäß Ihren spezifischen Anforderungen zu prüfen, empfehlen wir eigene Tests hinsichtlich der Eignung. Listen der verwendeten Testmedien stellen wir auf Wunsch zur Verfügung.

Bei dem vorliegenden Produkt handelt es sich in keiner Weise um Gefahrgut; gesonderte Behandlungshinweise entfallen daher.

Technische Änderungen sowie Irrtümer und Druckfehler vorbehalten!



Standard length *	app. 50 + 100 m (- 3 / + 5 m)
Standard width **	50, 70, 100 mm
Fabric	99/1% CO/PES L 1/1 18/14 – 20,2/20,2 Nm
Kind of coating	natural rubber
Hardness of coating	app. 42° Shore A (+/- 5°)
Colour	beige
Weight m ²	app. 1.600 g
Thickness	1,9 mm +/- 0,15 mm
<u>Tensile strength of fabric:</u>	
Warp	>1200 N/5 cm
Weft	>1100 N/5 cm
Adhesion strength (fabric/coating)	>90 N/5 cm
Heat resistance	app. 100 °C
Abrasion (DIN 53516)	<300 mm ³
<u>Resistance against:</u>	<input checked="" type="checkbox"/> acids <input checked="" type="checkbox"/> liquids <input checked="" type="checkbox"/> oil <input checked="" type="checkbox"/> grease <input checked="" type="checkbox"/> hot water
Special finish	-

* other length upon request
 ** other widths upon request

This information is provided to you for informatory and advisory purposes only and according to our best knowledge and experience. The content is however not legally binding. The provided data was obtained using internal test methods; however, we recommend that you carry out your own suitability tests in order to check the usability in accordance with your own specific requirements. We would be pleased to provide you with a list of the used test methods.

The described product does not fall under the rules of "dangerous goods"; no special handling information are needed.

Subject to technical alternations; errors and Omissions excepted!