



FRB-770III

Continuous Band Sealing Machine FRB-770 Series

Standard features

Voltage (V/Hz)	AC 220/50 110/60
Power (W)	50
Sealing Power (W)	300×2
Sealing Speed (m/min)	0-12 (0-16)
Sealing Width (mm)	10
Temperature Range (°C)	0-300
Printing Type	Embossing printing (optional)
Distance from Sealing Center to Conveyor Table (mm)	10-40
Conveyor Table Size (L×W) (mm)	840×153
Max. Conveyor Loading for Single Package (kg)	≤1
Overall Conveyor Loading (kg)	≤3
External Dimensions (L×W×H) (mm)	840×380×320
Net Weight (kg)	32



FRB-770I

Continuous Band Sealing Machine FRB-770 Series

Standard features

Voltage (V/Hz)	AC 220/50 110/60
Power (W)	50
Sealing Power (W)	300×2
Sealing Speed (m/min)	0-12 (0-16)
Sealing Width (mm)	10
Temperature Range (°C)	0-300
Printing Type	Embossing printing (optional)
Distance from Sealing Center to Conveyor Table (mm)	150-270
Conveyor Table Size (L×W) (mm)	840×153
Max. Conveyor Loading for Single Package (kg)	≤1
Overall Conveyor Loading (kg)	≤3
External Dimensions (L×W×H) (mm)	840×380×550
Net Weight (kg)	37



FRB-770II

Continuous Band Sealing Machine FRB-770 Series

Standard features

Voltage (V/Hz)	AC 220/50 110/60
Power (W)	50
Sealing Power (W)	300×2
Sealing Speed (m/min)	0-12 (0-16)
Sealing Width (mm)	10
Temperature Range (°C)	0-300
Printing Type	Embossing printing (optional)
Distance from Sealing Center to Conveyor Table (mm)	10-40
Conveyor Table Size (L×W) (mm)	840×153
Max. Conveyor Loading for Single Package (kg)	≤1
Overall Conveyor Loading (kg)	≤3
External Dimensions (L×W×H) (mm)	840×550×800
Net Weight (kg)	40