

PRODUCT DATA SHEET



NO-TOX[®] FOOD GRADE AIR LINE LUBRICANT

No-Tox Food Grade Air Line Lubricant, commonly known as No-Tox AL Lubricant, is a versatile lubricant for air lines and pneumatic tools found in the "clean" industries such as food, beverage, pharmaceutical and personal care product manufacturing. **No-Tox Food Grade Air Line Lubricant** is NSH H1 registered for use in applications where incidental food contact may occur. **No-Tox Food Grade Air Line Lubricant** is designed to maximize air tool life and optimize pneumatic system performance by reducing wear, corrosion and deposits. **No-Tox Food Grade Air Line Lubricant** contains an emulsifier to remove water from the air distribution system and to optimize tool performance.

Applications

- Pneumatic tools, air cylinders, air line lubricators, etc.
- Lightly loaded bearings

Features and Benefits

1 0	i catales and Denejus			
٠	NSF H1 registered	Use where incidental food contact may occur.		
٠	Bacteriological protection	Effectively inhibits the growth of certain bacteria, yeast and mold in the lubricant.		
٠	Compliances	Kosher and Pareve approved. Halal certified.		
٠	Leaves a strong film	Excellent metal wetting capabilities.		
٠	Excellent anti-wear performance	Reduces friction and wear.		
٠	Rust and oxidation stability	Maximizes air tool life.		

General Description

No-Tox Food Grade Air Line Lubricant is formulated for use in all air tools, air cylinders and lubricators. **No-Tox Food Grade Air Line Lubricant** is NSF H1 registered. **No-Tox Food Grade Air Line Lubricant** provides excellent film strength and anti-wear properties while eliminating deposit formation and tool sticking. **No-Tox Food Grade Air Line Lubricant** removes moisture from the air system optimizing tool performance. **No-Tox Food Grade Air Line Lubricant** is formulated with the highest quality USP white mineral oils and food grade additives that meet NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR, 178.3570. It is Kosher and Pareve approved, as well as Halal certified.

Product No. 62050

Page 1 of 2

1/3/2012

With continual research and development, Bel-Ray Company, Inc. reserves the right to change the information contained herein. The Company is not responsible for misuse or misapplication of its products.

NO-TOX[®] FOOD GRADE AIR LINE LUBRICANT

TYPICAL PROPERTIES

<u>Product No.</u>	<u>62050</u>
ISO Viscosity Grade	22
Viscosity, ASTM D445 @ 40°C, cSt @ 100°C, cSt	22.1 4.23
Viscosity, ASTM D2161 @ 100°F, SUS @ 210°F, SUS	116 40.5
Viscosity Index, ASTM D2270	90
Pour Point, ASTM D97 °C (°F)	-18 (0)
Falex EP Test, ASTM D3233, Method B Non-seizure load, lbf	1000
Flash Point, ASTM D92 °C (°F)	210 (410)
Rust Test, ASTM D665, Procedure A	Pass
Specific Gravity, ASTM D1298, 60/60°F	0.860
Density, ASTM D1298 @ 60°F, lb/gal	7.18
Appearance	Clear
Color	Water-white to pale yellow

1/3/2012

With continual research and development, Bel-Ray Company, Inc. reserves the right to change the information contained herein. The Company is not responsible for misuse or misapplication of its products.

Bel-Ray Company, Inc. • P.O. Box 526 • Farmingdale, NJ 07727 USA TEL +1 732-938-2421 • FAX +1 732-938-4232 • www.belray.com