


● FEATURES

1. 650TVL, 1/3" 960H CCD, **Effio-E DSP**
2. 6~50mm Varifocal Auto Iris Lens: Easy to Zoom, Easy to Focus
3. Color changes to B/W while IR LED and ICR start working
4. Constant current circuit design to make sure the life span of IR LED
5. Cable management :cable through bracket
6. ICR: No Color deflection under sunshine and halogen lamp
7. Viewing angle: Horizontal:46°~6°
8. Maximum Outdoor IR Range: 75~80M
9. **OSD, WDR**

Remark: Non-regulative adaptor may cause camera damaged.

● ACCESSORIES

1. Camera.....X1
2. User Manual.....X1
3. Screw.....X4
4. Plastic-Conical-Anchor.....X4
5. Mounting drawing paper.....X1
6. Hexagonal Wrench.....X1
7. Video Line.....X1
8. DC Connector.....X1



● SPECIFICATION

Item	CIR-UM36FGC
IP rating	IP66
Filter	Removable IR Cut Filter
Image Sensor	1/3" 960H CCD
Pixels	NTSC:1020(H)×508(V) PAL:1020(H)×596(V)
Horizontal Resolution	650 TVL
IR LED	190PCs IR LED
Vertical frequency	NTSC:60Hz PAL:50Hz
Horizontal Frequency	NTSC:15.734KHz PAL:15.625KHz
Clock Frequency	NTSC:28.636MHz PAL:28.375MHz
Scanning System	2:1 Interlace
S / N Ratio	≥52dB
Electronic Shutter	NTSC:1/60-1/100,000s PAL:1/50-1/100,000s
White Balance	Auto Tracking
Back Light Compensation	OFF
Auto Gain Control	ON
Gamma	0.45
Video Output	1V p-p,75Ω
Lens	6~50mm Varifocal Auto Iris Lens
Viewing Angle	Horizontal: 46°~6°
Power Supply	DC12V ±10%
Current Consumption	1350mA
Available IR Distance	75~80m(245.9~262.3ft)
Dimension	340×278×200mm (1.11×0.91×0.66ft)
Weight	2750g
Storage Temperature	-30~+60℃
Operating Temperature	-30~+40℃

● PACKAGE

Weight2750g
 Dimension 340×278×200mm
 Quantity per carton4PCs
 Dimension of carton.....610×370×595mm
 Weight of carton.....17.2KGs