

HV-4115



Main Feature

1/3" SHARP CCD sensor With cover,
 420 TV line, Day&Night, LED 20 pcs. 0 Lux
 15M IR On, Fixed Lens (3.6, 4 mm).
 more than 48 dB, AWB, BLC Auto,
 Power DC 12V / 300mA.

Specification



| | |
|----------------------|--|
| Model | HV-4115 |
| Image Device | 1/3" SHARP CCD sensor |
| Scanning Frequency | NTSC: 15,734KHz(H), 60Hz(V); PAL: 15,625KHz(H),50Hz(V) |
| Scanning System | NTSC: 525 line 2:1 interlace PAL:625 lines 2:1 interlace |
| Effective Pixels | NTSC: 500(H) x 582(V), PAL: 500(H) x 582(V) |
| Electronic Shutter | N:1/60- 1/100,000 sec (Auto); PAL:1/50-1/100,000sec (Auto) |
| Horizontal | 420 TV Lines, Day&Night |
| White-balance | Auto white balance (2500 °K~9500 °K) |
| Synchronizing System | Internal |
| Sensitivity | 0.1 Lux , 0 Lux at IR on / F2.0 |
| BLC | Auto |
| Signal to Noise | More than 48dB AGC off |
| IR Distance | 15 Meters (Max.) |
| IR LED | 20 pcs LED |
| IR Status | Under 1 0 Lux by CDS auto control |
| IR View Angle | View angle: 70 ° Beam spread: 40 °/per LED |
| IR Wavelength | 850nm - 25nm |
| LED Life | More than 10,000 hours |
| Lens | Fixed Lens (3.6, 4 mm) |
| Power Consumption | IR on: 180mA, IR off: 120mA(DC 12V) +- 5mA |
| Power Supply | 12VDC, 300mA |
| Power On | CDS Auto Control |
| Temperature | Operating: -10 to 50 °C |
| Video Output | Composite 1.0 Vp-p at 75 ohm |
| Construction | PVC Design |
| Dimensions | 115(W) X 75(H) mm |