

HV-4133



Main Feature

1/3" SHARP CCD With Cover,
 420 TV line, IP65, LED 88 pcs 840uM
 infrared LED, 0 Lux 40M IR On,
 Fixed (4,6,8 mm Optional) Day & Night,
 more than 48 dB, (ABW, BLC Auto),
 Power AC 240 AC.

Specification



Model	HV-4133
Image Device	1/3" SHARP CCD sensor
Scanning Frequency	NTSC: 15,734KHz(H), 60Hz(V); PAL: 15,625KHz(H),50Hz(V)
Scanning System	NTSC: 525 line 2:1 interlace PAL:625 lines 2:1 interlace
Effective Pixels	NTSC: 512(H) X 492(V); PAL: 512(H) X 582(V)
Electronic Shutter	N:1/60- 1/100,000 sec (Auto); PAL:1/50-1/100,000sec (Auto)
Horizontal	420 TV Lines
White-balance	Auto white balance (2500 °K~9500 °K)
Synchronizing System	Internal
Sensitivity	0.1 Lux , 0 Lux at IR on / F2.0
BLC	Auto
Signal to Noise	More than 48dB AGC off
AGC	Yes
Gamma Correction	0.45
IR Distance	40 Meters (Max.)
IR LED	88 pcs 840uM infrared LED
IR Status	Under 10 Lux by CDS auto control
IR View Angle	View angle: 70 ° Beam spread: 40 °/per LED
IR Wavelength	850nm - 25nm
LED Life	More than 10,000 hours
Lens	Fixed (4,6,8 mm Optional)
Power Consumption	R on: 1A, IR off: 70mA +- 5mA
Power Supply	110V ~ 240AC
Temperature	Operating: -10 to 50 °C
Video Output	Composite 1.0 Vp-p at 75 ohm
Construction	Aluminum
Dimensions	123(w) X 120(H) X 280(L) mm