

HV-4126VS



Main Feature

1/3" SONY CCD Sensor With Cover,
 420 TV line, IP65, LED 112 pcs.
 0 Lux 40-50M IR On, 4~9 Varifocal Lens
 Day & Night, more than 48 dB,
 (AWB, BLC Auto), Power AC 240 V.

Specification



| | |
|----------------------|------------------------------------------------------------|
| Model | HV-4126VS |
| Image Device | 1/3" SONY CCD sensor |
| Scanning Frequency | NTSC: 15,734KHz(H), 60Hz(V); PAL: 15,625KHz(H),50Hz(V) |
| Scanning System | NTSC: 525 line 2:1 interlace PAL:625 lines 2:1 interlace |
| Effective Pixels | NTSC: 512(H) X 492(V); PAL: 512(H) X 582(V) |
| Electronic Shutter | N:1/60- 1/100,000 sec (Auto); PAL:1/50-1/100,000sec (Auto) |
| Horizontal | 420 TV Lines |
| White-balance | Auto white balance (2500 °K~9500 °K) |
| Synchronizing System | Internal |
| Sensitivity | 0.1 Lux , 0 Lux at IR on / F2.0 |
| BLC | Auto |
| Signal to Noise | More than 48dB AGC off |
| AGC | Yes |
| Gamma Correction | 0.45 |
| IR Distance | 40-50 Meters (Max.) |
| IR LED | 112 pcs LED |
| IR Status | Under 10 Lux by CDS auto control |
| IR View Angle | View angle: 70 ° Beam spread: 40 °/per LED |
| IR Wavelength | 850nm - 25nm |
| LED Life | More than 10,000 hours |
| Lens | 4~9mm, Varifocal lens, AUTO IRIS |
| Power Consumption | IR on: 1A, IR off: 70mA +- 5mA |
| Power Supply | 12VDC, 110V ~ 240AC |
| Temperature | Operating: -10 to 50 °C |
| Video Output | Composite 1.0 Vp-p at 75 ohm |
| Construction | Aluminum |
| Dimensions | 131(w)x131(H) x300(L) mm |