

324 M10 Papai Sansai Chiang Mai 50210

Phone: 053-126-516 Mobile: 08-6420-3860 Fax: 053-126-517

[PEC@PE-ELECTRIC.COM](mailto:PEC@PE-ELECTRIC.COM)



เบรกเกอร์ ABB (XT1)

## รายละเอียดและราคา

Electrical Characteristics		XT1				
Rated uninterrupted current, I <sub>u</sub>		160 A.				
		XT1B	XT1C	XT1N	XT1S	XT1H
No. of Pole		3	3	3	3	3
Breaking capacity, I <sub>cu</sub>						
(AC) 50-60Hz 220/230V	[kA]	25	40	65	85	100
(AC) 50-60Hz 380/415V	[kA]	18	25	36	50	70
(DC) 250V-2 poles in series	[kA]	18	25	36	50	70
(DC) 500V-3 poles in series	[kA]	18	25	36	50	70
Breaking capacity, I <sub>cs</sub>						
(AC) 50-60Hz 220/230V	[kA]	100%	100%	75%	75%	75%
(AC) 50-60Hz 380V	[kA]	100%	100%	100%	100%	75%
Rate service voltage, U <sub>e</sub>						
	(AC) 50-60Hz [V]	690				
	(DC) [V]	500				
Overcurrent release/relay						
- TMD (ปรับตั้งกระแสใช้งานได้ตั้งแต่ 70-100% ของ I <sub>n</sub> )		•				
Basic dimensions						
Wide x Depth x Height	[mm]	76.2x70x130				
ราคาต่อหน่วย = บาท (3 Poles fixed version)						
Thermomagnetic						
	16[A]	4,150				
	20[A]	4,150				
	25[A]	4,150	4,700			
	32[A]	4,150	4,700	5,450		
	40[A]	4,150	4,700	5,450		
	50[A]	4,150	4,700	5,450	8,200	9,600
	63[A]	4,150	4,700	5,450	8,200	9,600
	80[A]	4,150	4,700	5,450	8,200	9,600
	100[A]	4,150	4,700	5,450	8,200	9,600
	125[A]	4,700	5,100	6,400	9,100	10,600
	160[A]	4,700	5,100	6,400	9,100	10,600

**\*\*\* ราคาหลังส่วนลดโปรดติดต่อสอบถาม \*\*\***

\*\*\*ราคานี้ยังไม่รวมภาษีมูลค่าเพิ่ม\*\*\*

\*\*\*บริษัทขอสงวนลิขสิทธิ์ในการเปลี่ยนแปลงราคาสินค้าโดยมิต้องแจ้งให้ทราบล่วงหน้า\*\*\*

---Price are not included VAT and Price are subjected to change without notice\*\*\*