



ชนิด (Type)	ลำตัวพินซ์ (Shank dia.) ØD	M	H	ชนิด (Type)	รูปร่างของปลายพินซ์ เลือกจากรูปหน้า 108-109 (For point, select from shape on page 108-109)
- Shoulder type -	D4~25	SKD11	60~63HRC	SP	
		SKH51	61~64HRC	SH	
		HAP40	64~67HRC	SPH	
- With center hole type -	D10~45	SKD11	60~63HRC	SP-C	
- With tapped type -	D5~25	SKD11	60~63HRC	MP	

Catalog No.			L	P•K max	P•W min.	B
Type	Shape	ØD				
D4-25 SP	2H~12H	4	(40) 50 60 70 80	3.90	2.00	8
		5		4.90	2.00	
		6		5.90	2.00	
SH	2J~18J	8	(40) (50) 60 70 80 90 100	7.90	2.00	13
		10		9.90	2.50	
SPH	3K~28K	13	(40) (50) 60 70 80 90 100	12.90	3.00	19
		16		15.90	4.00	
D10-45 SP-C	2L~7L	20	70 80 90 100 110 120	19.90	5.00	19
D5-25 MP	2M~14M	25		80 90 100 110 120	24.90	
		32	31.90		7.00	
		38	37.90		8.00	
		45		44.90	9.00	



Order

Catalog No.

SP3K

ØD -

25

L -

80

P•W•A•B•C•Q•R•S.....

P18.00 - W16.00 - A8.00

0.01 mm.

หมายเหตุ : ถ้า L = (40) ค่า B จะเท่ากับ 6 เท่านั้น (When L = (40), "B" value will be 6 uniformly)
ถ้า L = (50) ค่า B จะเท่ากับ 13 เท่านั้น (When L = (50), "B" value will be 13 uniformly)