

HI-6351

Main Feature

1/3" CMOS(PC3089K), 650 TVL 24pcs IR LED, 3.6mm/6mm lens optional, IR Distance: 20m, DNR,AGC,BLC Function, S/N Ratio 48dB, IP 66 ,Power Supply DC12V



Specification



| | |
|------------------------|----------------------------|
| Model | Hi-6351 |
| Pixel | 728(H)*488(V) |
| Sensor | 1/3" CMOS (PC3089K) |
| Scanning System | PAL/NTSC |
| Resolution | 650TVL |
| Min. Illumination | 0.05 Lux/IR On |
| DNR | Auto |
| S/N Ratio | ≥48dB |
| Video Output | 1.0Vp-p/75Ω |
| AGC | Auto |
| White Balance | Auto |
| Backlight Compensation | Auto |
| Exposure Mode | Electronic Exposure |
| Electronic Shutter | 1/50(1/60) ~1/10000 Second |
| Gamma Correction | 0.45 |
| Sync. System | Internal |
| Lens | 3.6mm/6mm optional |
| Lens Mount | M12 |
| IR Led | 24pcs S5 IR Led |
| IR Distance | 20M |
| IP Rank | 66 |
| Material/Color | Metal / Matt finish white |
| Work Humidity | ≤90%RH |
| Operation Temperature | -10℃~+50℃ |
| Power Supply | DC 12V /5% |
| Power Consumption | ≤2W |
| Dimension | 148(L)* 53.9(S)*70 (H)/mm |
| Gross Weight | 0.36kg |

