

T-330 AH
**SATURATED STEAM 17 BAR
(250 PSI)**
**NFT 47263 CAT I TYPE 3 BS
5342/2 CLASS A DIN 2825**


TUBE	BLACK EPDM
REINFORCEMENT	HIGH TENSILE STEEL CORDS
COVER	RED EPDM - HEAT, ABRASION AND OZONE RESISTANT - PIN PRICKED
APPLICATION	SATURATED STEAM FOR USE IN REFINERIES, SHIPYARDS, CHEMICAL PLANTS AND ALL INDUSTRIAL APPLICATIONS.
TEMPERATURE	-40°C +208°C (-40°F +406°F)
BRAND TEXT	ALFAGOMMA -ITALY- T-330 17 BAR (250 PSI) STEAM - DRAIN AFTER USE- BS 5342/A/2-NFT47263 CI T3 DIN2825 q/yy
BRAND TYPE	EMBOSSSED
NOTE	DIAM. 63mm AND 76mm NOT COVERED BY ABOVE MENTIONED NORMS
APPROVALS	
SAFETY FACTOR	10:1

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
330AH010223YA3	10	3/8	22	6	510	17	250		100	61	61
330AH013253YA3	13	1/2	25	6	580	17	250		130	15,25/30,5/61	61
330AH016283YA3	16	5/8	28	6	640	17	250		160	61	61
330AH019323YA3	19	3/4	32	6,5	750	17	250		190	15,25/30,5/61	61
330AH019333YA3	19	3/4	33	7	870	17	250		190	61	
330AH025383YA3	25	1	38	6,5	940	17	250		250	15,25/30,5/61	61
330AH025403YA3	25	1	40	7,5	1080	17	250		250	61	
330AH032463YA3	32	1 1/4	46	7	1390	17	250		320	61	61
330AH032483YA3	32	1 1/4	48	8	1560	17	250		320	61	
330AH038523YA3	38	1 1/2	52	7	1610	17	250		380	61	61
330AH038543YA3	38	1 1/2	54	8	1810	17	250		380	61	
330AH051673YA3	51	2	67	8	2240	17	250		510	61	61
330AH051693YA3	51	2	69	9	2490	17	250		510	61	
330AH063833YA3	63	2 1/2	83	10	3830	17	250		630	30,5	30,5
330AH076963YA3	76	3	96	10	4540	17	250		760	30,5	30,5