

SDR-H6104AHD

Dual Streaming 720P Real Time H.264 Multiplex
4ch 720P Economical AHD DVR

TELCA



FEATURE

- 4ch 720P Economical AHD DVR
- Support 1 HDD, Max 4TB
- 4 full channel realtime playback
- Support Icon Interface, User Friendly & Easy-Operate
- Quick Backup when Playback
- Support HDMI/VGA Simultaneous Output
- Support PTZ, Manual Alarm, Alarm In/Out
- Support CMS, Web View and Mobile View



AHD DVR

SPECIFICATIONS

| | |
|--------------------------|--|
| Model | SDR-H6104AHD |
| Housing Height | K (Mini 1U) |
| Operation System | Embedded Linux |
| Video Compression | H.264 |
| Video Input | 4 CH |
| Video Output | 1VGA, 1 HDMI |
| Analog HD (AHD) | Support (Two CH in one Group, same 720P or 960H) |
| Audio Compression | G.711A |
| Audio Input | 2 Ch RCA (1K Ω , Vp-p = 2.0V Line) |
| Audio Output | 1 Ch RCA (600 Ω , Vp-p = 2.0V Line) |
| Audio Bidirectional Talk | 3.5 mm MIC Input Interface |
| Alarm Input | 4 |
| Alarm Output | 1 |
| Preview Resolution | VGA/HDMI = 1920x1080 |
| Display mode | Full screen/Multi-screen |
| Sequence | Yes |
| Recording Resolution | 4*720@25fps(Auto, Default) or 4*960H@25fps |
| Recording Mode | Manual, Schedule, Motion, Alarm |
| Recording Interval | Pre-record: 5~30 sec., Post-record: 0~180 sec |
| Playback Channel | 4*720@25fps(Auto, Default) or 4*960H@25fps |
| Search mode | Time, Date, Record Mode |
| Remote Operation | WEB (IE, Chrome, Firefox) |
| Mobile | Support (iPhone, Android, iPad) |
| Backup | USB device & Network download |
| HDD | 1 HDD (Max support 4TB) |
| Network Interface | 1 RJ45 1000M Adaptive Ethernet Interface |
| USB Interface | 2 Interfaces (Mouse control & Backup) |
| Auxilliary Interface | 1 RS-485 (half-duplex) |
| Power Supply | DC 12V |
| Power Consumption | 24W |
| Working Environment | -10°C ~ +45°C / 15% ~ 85% RH |
| Dimension | 254mmx168mmx45mm (WxDxH) |
| weight | 0.8 KG (without HDD) |

AHD DVR