

**806AA**  
**FLEXOR 6**  
**SAE 100 R6 - EN 854 R6**



<b>Tube</b>	OIL RESISTANT SYNTHETIC RUBBER
<b>Reinforcement</b>	ONE HIGH TENSILE TEXTILE BRAID
<b>Cover</b>	ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER
<b>Application</b>	LOW PRESSURE HIDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER. SPECIALLY DESIGNED FOR USE IN "PUSH ON" APPLICATIONS
<b>Constant operation</b>	-40°C +100°C (T max air = +70°C)
<b>Ambient temperature</b>	-40°C +80°C
<b>Fittings</b>	Consult fittings catalogue
<b>Length</b>	Random
<b>Branding</b>	ALFAGOMMA FLEXOR 6 ID... - WP ... MPa (... PSI) - SAE 100R6-EN854 R6 -DN ... - Q/yr
<b>Note</b>	* Alfagomma proprietary hose Not listed in SAE J517 100 R6 spec. S.F.: 4:1

Code	ID mm	ID in	Dash	OD mm	OD in	WP Mpa	WP psi	BP Mpa	BP psi	BR mm	BR in	Weight kg/m	Weight lb/C ft
806AA006008JA8	6	1/4	-4	12,7	0,5	2,8	400	11	1600	64	2,6	0,13	9
806AA008008JA8	8	5/16	-5	14,3	0,56	2,8	400	11	1600	76	3	0,13	9
806AA010008JA8	10	3/8	-6	15,9	0,63	2,8	400	11	1600	76	3	0,17	11
806AA012008JA8	13	1/2	-8	19,8	0,78	2,8	400	11	1600	102	4,1	0,23	15
806AA016008JA8	16	5/8	-10	23	0,91	2,4	350	10	1400	107	4,3	0,27	18
806AA020008JA8	19	3/4	-12	26,9	1,06	2,1	300	8	1200	152	6,1	0,37	25
806AA025008JA8*	25	1	-16	33,4	1,31	1,7	250	7	1000	203	8,1	0,49	33