



## Auto-cutter Equipped 2 inch Thermal POS Printer

# SRP-150

*BIXOLON SRP-150 POS printer offers a proven and reliable printing solution.*

### HIGHLIGHTS

- Fast printing speed (up to 70mm/sec)
- Built-in power supply
- Much less noise
- Simple and Modern design
- Long lasting auto-cutter up to 1 million cuts with easy paper-jam removal
- Paper roll diameter : Max. Ø 80mm
- Different printing density by dip switch setting
- Customer oriented software tools provided
  - Firmware download
  - NV image download

### PRODUCT FEATURES

#### Long-lasting auto-cutter

The Auto-cutter of the SRP-150 has long lifespan up to 1 million cuts. It has specially designed components such as gears, cutting blade and covers to guarantee its lifetime. In addition, it also has a manual button conveniently positioned for easy clearing of the paper jam.



*Reliable Auto-cutter*

#### Built-in power supply

The AC / DC adapter is elegantly integrated into the compact printer housing. Consequently, messing around with cables is avoided which is ideal at space-limited POS terminals or highly frequented cash desks.



*Built-in Power Supply*

#### Paper Roll Diameter

Print lasts longer with a bigger paper diameter up to Max. Ø 80mm.



*Bigger Paper Roll*

### SPECIFICATIONS

#### PRINT

- PRINTING METHOD : Direct thermal
- PRINTING SPEED : 70mm/sec
- RESOLUTION : 203dpi (8 dot/mm)
- CHARACTER SIZE (W X H dots) : Font A: 12 X 24 Chinese: 24 X 24
- CHARACTERS PER LINE : Font A : 32
- CHARACTER SET : Alphanumeric Character : 95  
Extended Character : 128 X 34 pages  
International Character : 32
- BARCODES  
1D : EAN-13, EAN-8, Code 39, Code 93, Code 128, ITF, Coda Bar, UPC-A, UPC-E  
2D : PDF417, QR Code

#### PAPER

- WIDTH : 58mm
- PAPER ROLL DIAMETER : Max. Ø 80mm
- PAPER LOADING : Easy paper loading

#### RELIABILITY

- PRINTER UNIT : 20 million lines
- TPH : 50 Km
- AUTO CUTTER : 1 million cuts

**INTERFACE** : Serial(RS-232C), Parallel (IEEE1284), USB

**RECEIVE BUFFER** : 4 Kbytes

**EMULATION** : BXL / POS

**DRIVER** : Windows Driver

**SENSOR** : Paper End Sensor, Cover Open Sensor

**DRAWER PORT** : 1 port

**POWER SUPPLY (ADAPTER)** : AC 100V ~ 240V/ DC12V±5%,3A

**DIMENSIONS** : 131 X 194.5 X 124 (W X L X H mm)

**OPERATING TEMPERATURE** : 0~45°C



#### BIXOLON Co.,Ltd.

7-8th FL, Miraeasset Venture Tower, 685, Sampyeong-dong,  
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, KOREA (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

#### BIXOLON America Inc.

3171 Fujita St Torrance,  
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

#### BIXOLON Europe GmbH

Tiefenbroicher Weg 35,  
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de