



Series
MDPC

Mini Digital Pressure Controller

Small, Lightweight, 6 Selectable Pressure Units



The Series MDPC is a slim, gas pressure sensor that is small in size and light in weight. This pressure controller supports many installation methods and features high measurement accuracy. This small controller yields excellent stability, high shock and vibration resistance. The MDPC also provides good over-load capacity and heat resistance. It can be utilized in many industries such as: high-tech electronics, general processing, food packaging and automatic assembly. The MDPC features 6 user selectable pressure units and a large, LED 3-color display with selectable color options that allow for easy reading. Changing units is simple, and by using the included unit stickers, the pressure unit displayed becomes very clear. The fast parameter copy function makes copying parameters to other MDPC pressure controllers effortless. The key lock mode also prevents any unnecessary changes to the parameters, which can have an effect on the operation. Another characteristic of this multi-talented pressure controller is its ability to detect both positive and negative pressure. The MDPC is available in NPN, PNP, analog voltage or current output control modes.

Model	Range psi (kPa)	Switch Output	Retransmission
MDPC-112	-14.5 to 14.5 (-100 to 100)	NPN	4 to 20 mA
MDPC-122	-14.5 to 14.5 (-100 to 100)	NPN	1 to 5 V
MDPC-132	-14.5 to 14.5 (-100 to 100)	PNP	4 to 20 mA
MDPC-142	-14.5 to 14.5 (-100 to 100)	PNP	1 to 5 V
MDPC-212	-14.5 to 145 (-100 to 1000)	NPN	4 to 20 mA
MDPC-222	-14.5 to 145 (-100 to 1000)	NPN	1 to 5 V
MDPC-232	-14.5 to 145 (-100 to 1000)	PNP	4 to 20 mA
MDPC-242	-14.5 to 145 (-100 to 1000)	PNP	1 to 5 V

OPTION

For NIST traceable calibration certificate, use order code NISTCAL-PT1.

SPECIFICATIONS

Service: Non-corrosive gas.

Wetted Materials: Brass with nickel plating.

Housing Materials: Polycarbonate, polybutylene terephthalate.

Accuracy: ±3% of full range.

Pressure Limits:

MDPC-1: 29 psi (200 kPa);

MDPC-2: 217.6 psi (1500 kPa).

Temperature Limits:

Operating: -40 to 185°F (-40 to 85°C);

Storage: -4 to 149°F (-20 to 65°C);

Ambient: 32 to 122°F (0 to 50°C).

Display: 2-line LCD display, 4 digits for measured value and 3.5 digits for setup display.

Power Requirements: 12 to 24 VDC ±10% no isolations.

Power Consumption: 40 mA max.; Current output type 60 mA max.

Series MDPC, Mini Digital Pressure Controller

ACCESSORIES

A-152, Bracket installation kit

A-153, Panel installation kit

Process Connections: 1/8" NPT, inner connection M5, for 1/8" PT contact factory.

Weight: 1.3 oz (36.85 g).

Agency Approvals: CE: MDPC-121, MDPC-122, UL.

SWITCH SPECIFICATIONS

Switch Type: NPN or PNP.

Electrical Rating: 100 mA @ 30 VDC.

Response Time: Programmable to 2ms, 4ms, 10ms, 30ms, 50ms, 100ms, 250ms, 500ms, 1000ms or 5000ms.

Display Cycle: Programmable to 100ms, 250ms, 500ms or 1000ms.

TRANSMITTER SPECIFICATIONS

Output Signal:

1 to 5 V: Minimum output load resistance 1000 Ω;

4 to 20 mA: Maximum output load resistance 400 Ω.

Zero and Span Adjustments: Menu scalable within the range.