

Air Dryer

*Electricity-Free and
Pneumatically Operated*



● Pressure gauge.

● 3 outlet ports.
● Extended use
(1 to 3).

● Air intake.

● Automatic draining
quick-release port.
● Connect to OD12mm
draining horse.



More information



See Test Video



AD-1800



AD-2800



Advantages

- Electricity-free ; no utility fee.
- For a IHP freeze dryer and its necessary accessories, the utility fee can be more than USD500 per year, (EX: 1.3KW/h x 8h (per day) x 30days (per month) x 12 months x \$USD 0.14 = \$USD 524.16)
- No filter. No extra cost for any consumables.
- No public safety issue.
- Driven by compressed air.
- Only half size of other similar devices.
- Light weight ; the heaviest one is only 10 kg (22 LB).
- Water separation rate is up to 99%.
- Air Dryer works by centrifugal force at high rpm.
- Extremely durable ; long product life.
- The condensation will be drained automatically as it accumulates to a certain level.
- Almost no pressure drops in air system when the unit is running.

Air Dryer	Process Flow Rate (L/Min.)	N. W.	Output port	Machine Dimensions (mm)
AD-1800	1800	2.4 kg / 5.3 lb	1	210W×90D×370H
AD-2800	2800	10 kg / 22 lb	3	310W×160D×560H



HOLD WELL INDUSTRIAL CO., LTD.

31, Aly. 10, Ln. 120, Sec. 2, Yahuan Rd., DaYa Dist.,
Taichung City 42869, Taiwan (R.O.C.)
sales@holdwell.com