

VERY HIGH RELIABILITY, VERY GOOD PRICE!

TIGSTAR PRO

The new generation of GCE TIG Brenner with extraordinary technical characteristics at a very good PRICE! They're provided with a very slim and ergonomic shank, a ball joint at the handle and an ultra soft leather protection for cable (n/a on V version) making them fully handy. Available in two variants: Air cooled and water cooled. The spare parts are fully compatible with standard market Brenner.

FEATURES

- Optimum cooling (Air or Water)
- Very slim and ergonomic handle.
- Ball joint at the handle improving the handling
- Standard trigger version or knob version (model V)
- Plug TIG included (G1/4 - G3/8 - quick connection)
- Soft leather cover for cable (n/a on V version)
- Provided with a spare parts set (ceramic nozzle, collet body, collet, back cup long)



Very flexible



THE ONLY ONES WITH LEATHER CLAD CABLE!

The first 75cm of torch cable nearest to operator are clad in soft leather (n/a on Brenner with knob control valve).

This gives great flexibility of movement and very good protection against spatter.

AIR COOLED



MAXIMUM EASY USE!

All TIGSTAR Brenner are delivered complete with connection. The gas connections included in the box are for all possible needs (1/4 or 3/8 or quick)

Art. Nr.	Descr.	Duty Cycle DC 35%	Duty Cycle AC 35%	Ø	Ø	Qt.	Stock class
415P09C104N	TIGSTAR PRO 9 4M	110A	95A	0,5-1,6	25 mm (small)	1	DFW
415P09C108N	TIGSTAR PRO 9 8M	110A	95A	0,5-1,6	25 mm (small)	1	MTO
405P09V104N	TIGSTAR PRO 9 V 4M	110A	95A	0,5-1,6	25 mm (small)	1	DFW
415P17C104N	TIGSTAR PRO 17 4M	140A	125A	0,5-2,4	25 mm (small)	1	DFW
415P17C114N	TIGSTAR PRO 17 4M	140A	125A	0,5-2,4	35 mm (big)	1	DFW
415P17C108N	TIGSTAR PRO 17 8M	140A	125A	0,5-2,4	25 mm (small)	1	DFW
405P17V104N	TIGSTAR PRO 17 V 4M	140A	125A	0,5-2,4	25 mm (small)	1	DFW
405P17V114N	TIGSTAR PRO 17 V 4M	140A	125A	0,5-2,4	35 mm (big)	1	DFW
415P26C104N	TIGSTAR PRO 26 4M	180A	150A	0,5-4,0	35 mm (big)	1	DFW
415P26C108N	TIGSTAR PRO 26 8M	180A	150A	0,5-4,0	35 mm (big)	1	DFW
405P26V104N	TIGSTAR PRO 26 V 4M	180A	150A	0,5-4,0	35 mm (big)	1	DFW

WATER COOLED



V version (with knob valve)

Art. Nr.	Descr.	Duty Cycle DC 100%	Duty Cycle AC 100%	Ø	Ø	Qt.	Stock class
415P20C104N	TIGSTAR PRO 20 4M	250A	220A	0,5-3,2	35 mm (big)	1	DFW
415P20C108N	TIGSTAR PRO 20 8M	250A	220A	0,5-3,2	35 mm (big)	1	DFW
415P18C104N	TIGSTAR PRO 18 4M	320A	240A	0,5-4,0	35 mm (big)	1	DFW
415P18C108N	TIGSTAR PRO 18 8M	320A	240A	0,5-4,0	35 mm (big)	1	DFW



EN 60974-7

