

### 2 Megapixel Bullet IR Network Camera



IP Camera

## FEATURE

- 1/2.9" 2M SONY Exmor CMOS Sensor
- H.264 Encoding, Max Resolution 1920\*1080
- 80db D-WDR, 2D/3D DNR
- Dual stream, motion detection, PSW protection
- 2Pcs Array leds , IR distance 30M
- Weatherproof Aluminium Housing IP66
- Support ONVIF protocol interface



## SPECIFICATIONS

Camera	
Image Sensor	1/2.9" 2M SONY Exmor CMOS Sensor
Min Illumination	0.01Lux@F1.2 (0Lux,IR on)
WDR	≥80dB
Lense Type	3.6mm Fixed Lens
Day & Night	Auto(ICR)
IR LEDs	2 pcs IR Array , IR distance 30M
Video	
Video Compression Standard	H.264/M-JPEG
Resolution (Main Stream)	920*1080/1280*960/1280*720/704*480, 1-25(30)fps
Resolution (Substream1)	704*480/640*480/352*240
Resolution (Substream2)	1280*720/960*540/640*480
Video Compression	64Kbps-8Mbps Continuously adjustable, Support CBR/VBR
Network Function	
Protocols	TCP/IP, UDP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, FTP, UPNP, NTP
Compliance	ONVIF2.4
Mobile phone	iPhone, iPad, Android
Communication Interface	1 RJ45 10M/100M Ethernet port
General	
Input Voltage	12 VDC ± 10%
Working temperature / Humidity	-10°C - 50°C / 0% - 90%
Weight	380g