



Electrical Insulating Rubber Mat

Up To 115 kv

Material's Property

Properties	Values
Hardness	65 ± 5 Shore A
Tensile Strength	> 70 kg / cm ²
Elongation at Break	> 250 %
Specific Gravity	1.30 - 1.35
Service Temperature	-30 to +100°C
Surface	Smooth
Color	Black
Lifespan	3-5 years
Test Certificate	Yes (ASTM / IEC)



No	Thickness (mm)	Width (M)	Class (IEC61111: 2009)					Maximum Use Voltage(V)	Length/Roll (M)
			0	1	2	3	4		
1	2	1/1.2/1.4/1.5	✓	✓				7,500	1-30
2	3	1/1.2/1.4/1.5	✓	✓	✓			17,000	1-20
3	4	1/1.2/1.4/1.5	✓	✓	✓			17,000	1-10
4	5	1/1.2/1.4/1.5	✓	✓	✓			17,000	1-10
5	6	1/1.2/1.4/1.5	✓	✓	✓	✓		26,500	1-10
6	8	1/1.2/1.4/1.5	✓	✓	✓	✓		26,500	1-5
7	10	1/1.2/1.4/1.5	✓	✓	✓	✓	✓	36,000	1-5
8	12	1/1.2/1.4/1.5	✓	✓	✓	✓	✓	> 65,000	1-5
9	14	1/1.2/1.4/1.5	✓	✓	✓	✓	✓	> 65,000	1-5
10	20	1/1.2/1.4/1.5	✓	✓	✓	✓	✓	Up to 115,000	1-3.5
11	25	1/1.2/1.4/1.5	✓	✓	✓	✓	✓	Up to 115,000	1-3.5

ท่านสามารถสอบถามข้อมูลเพิ่มเติมหรือสั่งซื้อสินค้าผ่านช่องทาง

Tel : 0 2408 2583-4 , 09 8289 8676 LINE@ : @ptirubber Technical Engineer Tel: 08 6307 7319

Email : ptiproduct@hotmail.com , sales@polytechindustry.co.th Website : <https://electromerpti.com>