

# SPECIFICATION

D-7

## Face Mask 3 Ply for PM2.5



### **Description :**

**F**ace Mask 3 ply is made of polypropylene spunbond and meltblown nonwoven fabrics with adjustable nose strip and flat or elastic ear-loop to give basic protection to the user. It's mainly used in medical, dental, cleanroom, critical environment, food handling / production and Industrial manufacturing.

### **Measurement of finished face mask :**

Mask Length	: 175 ± 1 mm.
Width	: 95 ± 1 mm.
Elastic band	: 180 mm. ± 1 per piece
Color available	: Black
Standard Packaging	: 50 pcs. / bag , 20 bag / carton

### **Materials :**

1 <sup>st</sup> layer	: Polypropylene Spunbond Non-woven Fabric
2 <sup>nd</sup> layer	: Meltblown Filter Non-woven
3 <sup>rd</sup> layer	: Polypropylene Spunbond Non-woven Fabric
Nose strip	: Aluminum wire covered PVC
Ear-loop	: Elastic

### **Benefit :**

- Particle Filtration Efficiency (PFE) > 99%, Bacterial Filtration Efficiency(BFE) > 99%
- Excellent breathability
- Non irritating, fiber glass free fabric
- Polypropylene Spunbond Non-woven 100%
- Hypoallergenic suitable for medical
- Hygienic
- Splash resistant
- Ultrasonic welding manufacturing process



Distributed by : DSI Corporation Co.,Ltd.  
Tel. 02 993-4692-9 , E-mail: [cs@dsicorp.co.th](mailto:cs@dsicorp.co.th) , [www.dsicorp.co.th](http://www.dsicorp.co.th)

R.01/06022020