

IM-215

21.5" True Flat Industrial Touch Monitor

Preliminary



Features

- 21.5" 16:9 LCD panel with LED backlight with 50,000 service life
- 10-point PCAP touchscreen
- Anti-fingerprint surface treatment for ease of cleaning and enhanced readability
- Wide viewing angles support for both portrait and landscape modes
- IP rating for water and dust protection

Ordering Information

- IM-215
21.5" True Flat Industrial Touch Monitor

Optional Accessories

- AC Adapter

Specifications

Model	IM-215
Display	
Size	21.5"
Resolution	1920 x 1080
Aspect Ratio	16:9
Color	16.7M
Brightness (Nits)	400 nits (w/ touch)
Backlight Life (Hrs)	50,000
Viewing Angle (U/D/R/L)	89/89/89/89
Contrast Ratio	1000:1
Touchscreen	10-point, PCAP, Anti-fingerprint coating
Bonding	Air bonding
I/O	
USB Port	USB type B(for touch)
Video	HDMI x1, VGA x 1
Audio	w/o Audio
Environmental	
Operating Temperature	0°C to 60°C
Storage Temperature	-20°C to 60°C
Humidity	10% to 80% @ 40°C (non-condensing)
Surface Hardness	7H
Vibration	Operating: 1G random 5 to 500Hz
Shock	Operating: 20G acceleration part to part, 11ms
IP Rating	Front IP65
Certifications & Compliance	CE/FCC/BSMI
Power Input	DC-12V 5A Max.
Power Consumption	24.5W Max.
Mechanical	
Weight	4.8
Dimensions (H x W x D)	520 x 310 x 50 mm
Mounting	VESA Mount, MIS-D 75mm x 75mm, 100mm x 100mm (Standard)

Dimensions

